

PiBox - Bug #370

Need to patch config.txt in the firmware to set overscan

30 Jul 2014 17:05 - Hammel

Status:	Closed	Start date:	30 Jul 2014
Priority:	Immediate	Due date:	
Assignee:	Hammel	% Done:	100%
Category:	02 - GPU Firmware	Estimated time:	0.00 hour
Target version:	0.9.0		
Severity:	02 - High		
Description			
<p>The overscan isn't set properly for the TV I'm testing on. The config.txt pulled from the firmware package should be updated to fix this. The updates are on the current test distro. I should just create a patch and apply it when the firmware target is run.</p> <p>Note that if I can find a way to have the config.txt also force audio output to the Pi port (instead of HDMI) I should do that too.</p>			

Associated revisions

Revision f2375c49 - 31 Jul 2014 15:57 - Hammel

RM #370: Updated the overscan settings. Added comments related to addressing audio output (RM #357).

History

#1 - 31 Jul 2014 15:58 - Hammel

- Status changed from New to Closed

- % Done changed from 0 to 100

config.txt is actually in the PiBox source tree, so I don't need a patch. I just update that file with the overscan options. This has been done and pushed upstream.

Additional information on how to use this file has been added to it in order to test some options related to sound output.

Closing issue.