

monkey - Bug #422

Reinstallation of monkey trashes auth file

18 Dec 2014 13:17 - Hammel

Status:	Closed	Start date:	18 Dec 2014
Priority:	Urgent	Due date:	
Assignee:	Hammel	% Done:	100%
Category:		Estimated time:	0.00 hour
Target version:	0.10.0		
Severity:	03 - Medium		

Description

The pibox.mk file gets overwritten on a reinstall of the monkey package. To fix this:

1. Move pibox.mk pibox.mk.pkg in the source tree
2. install pibox.mk.pkg
3. Add the following line to postinst for the package, but only if /etc/monkey/plugins/auth/pibox.mk doesn't already exist

```
mv /etc/monkey/plugins/auth/pibox.mk.pkg /etc/monkey/plugins/auth/pibox.mk
```

Associated revisions

Revision fdfa8564 - 19 Dec 2014 11:43 - Hammel

RM #422: Install users.mk as pibox.mk.pkg and then move it to pibox.mk only if that file doesn't already exist.

History

#1 - 19 Dec 2014 11:46 - Hammel

- Status changed from New to Closed

- % Done changed from 0 to 100

Install users.mk as pibox.mk.pkg and then move it to pibox.mk only if that file doesn't already exist.

Tested on target, committed and pushed upstream.

Closing issue.