

PiBox - Bug #550

Pulling USB media stick may not cause umount

18 Sep 2016 17:57 - Hammel

Status:	Closed	Start date:	18 Sep 2016
Priority:	Immediate	Due date:	
Assignee:	Hammel	% Done:	100%
Category:	04 - Root File System	Estimated time:	0.00 hour
Target version:	0.12.0		
Severity:	02 - High		
Description			
I seem to have left over mounts of USB sticks after they have been pulled. The event processing must not be working.			

Associated revisions

Revision 528306b0 - 02 Jan 2017 16:55 - Hammel

RM #550: Fix BASE default path to remove the trailing slash. That fixes umounts when the stick is pulled.

History

#1 - 20 Dec 2016 20:32 - Hammel

- % Done changed from 0 to 30

I think the problem here is this line in blockhandler.sh:

```
| BASE=/media/
```

It should be

```
| BASE=/media
```

The way it is now leaves an entry like this in STATEF:

```
| /media//usb/sdb1
```

When the remove searches for this the double slashes fail so the umount doesn't run. If it isn't BASE then it's related to having that trailing slash on BASE.

Need test this on hardware to make sure that's the problem.

#2 - 22 Dec 2016 16:40 - Hammel

- % Done changed from 30 to 70

That worked. Will check in the change later.

#3 - 07 Jan 2017 17:43 - Hammel

- *Status changed from New to Closed*

- *% Done changed from 70 to 100*

Committed and pushed. Closing issue.